



1.27PH 簡牛系列--配合母座(DW2127系列)

Pitch : **1.27PH**

PIN 數: 10P.12P.14P.16P.18P.20P.22P.24P.26P.30P.32P.40P.
42P.44P.50P.60P.64P.70P.80P.90P.100P

型體 : 公模多款型體 [無柱. 有柱(5.65T, 5.4T)]

塑品材質: 符合RoHS 環保規範 , 高溫塑料Nylon 6T. 9T. LCP工程塑料.. 等

塑品色系: 黑 端子尺寸: □ 0.4±0.005mm四方針 (建議電鍍後尺寸)

外型尺寸:



5.65T	膠寬 : 5.65 mm ± 0.1 膠高 : 5.65mm ± 0.1	Φ 1.15 & Φ 0.8 柱腳高度 1.05
5.4T	膠寬 : 5.65 mm ± 0.1 膠高 : 5.4mm ± 0.1	Φ 1.15 & Φ 0.8 柱腳高度 1.05

膠長尺寸如下: (各公差為:± 0.15)

PIN數	膠長	PIN數	膠長	PIN數	膠長	PIN數	膠長
10P	9.41mm	34P	24.65mm	58P	39.89mm	82P	55.13mm
12P	10.68mm	36P	25.92mm	60P	41.16mm	84P	56.40mm
14P	11.95mm	38P	27.19mm	62P	42.43mm	86P	57.67mm
16P	13.22mm	40P	28.46mm	64P	43.70mm	88P	58.94mm
18P	14.49mm	42P	29.73mm	66P	44.97mm	90P	60.21mm
20P	15.76mm	44P	31.00mm	68P	46.24mm	92P	61.48mm
22P	17.03mm	46P	32.27mm	70P	47.51mm	94P	62.75mm
24P	18.30mm	48P	33.54mm	72P	48.78mm	96P	64.02mm
26P	19.57mm	50P	34.81mm	74P	50.05mm	98P	65.29mm
28P	20.84mm	52P	36.08mm	76P	51.32mm	100P	66.56mm
30P	22.11mm	54P	37.35mm	78P	52.59mm		
32P	23.38mm	56P	38.62mm	80P	53.86mm		

****其他特殊規格,歡迎洽詢.**

東吳精密工業股份有限公司 E-mail:dw.dw@msa.hinet.net
TEL:886-2-2278-2045(代表號) ; FAX:886-2-2278-2047

